

Hydroblaster Pressure Washer

5/3000 G - Engine Driven, Cold Water Pressure Washer

Hydroblaster 5/3000G engine-driven, high-pressure cold water systems provide flow of 5-gpm with variable pressure up to 3000-psi. Hydroblaster G system design and quality manufacturing ensures continued performance, reliability and safety. All G model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

- Formed Steel Base W/ Forklift Slots
- Full Steel Cage Protection
- 6 Gallon Carb Compliant Fuel Tank
- Belt Driven Pump
- Trigger Gun
- Variable Pressure Wand
- Downstream Chemical Injection
- 50' (15M) High Pressure Discharge Hose
- 15-Degree Nozzle
- Portability Kit - Casters

Optional Features

- Battery - Lead Acid
- Battery - Spiral Cell
- Pressure Gauge
- Hour Meter
- Nozzle Sets
- [Turbo Nozzle](#)
- Hose Reel
- Discharge Hose Lengths

Specifications

Volume - GPM (LPM)	5 (18.9)
Pressure - PSI (BAR)	3000 (207)
Gasoline Engine - HP	19
Dimensions, Inches (mm)	38 (965) L X 18 (457) W X 27 (686) H
Weight, Lbs (kg)	435 (197)



Pricing

For complete pricing details,
Submit a quote online below.

[Get a Quote](#)