



Hydroblaster Pressure Washer

7/3000 EHOV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 7/3000EHOV high-pressure hot water systems provide flow of 7GPM with variable pressure up to 3000PSI. All EHOV systems can be configured to be heated by a variety of oils, including kerosene, diesel, and JP fuels. Systems employ high-efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHOV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

208/230 Volt

Hinged Access Equipment Enclosure Premium Efficiency Drive Motor Belt Driven Pump Schedule 80 Coil With Extended Warranty Automatic System Shutdown Timer Automatic Burner Ignition and Controls 6 Gallon Front Fill Fuel Oil Tank Low Fuel Level Burner Lockout w/ Indicator Trigger Gun System Discharge Control Dual Nozzle Variable Pressure Wand

Optional Features

Suitable For a Variety of Power Supplies Including 50Hz Lockable Power Disconnect Switch Hour Meter, Pressure and Temperature Gauges Trigger Actuated Start Remote Control Station In NEMA 4X Enclosures Stainless Trim; Pump Enclosure and Coil Housing Nozzle Options including Turbo Nozzle Discharge Soap/Chemical Injection Precision (Peristaltic Pump) Inlet Soap Soap Injection Flow Meter Plastic Float Tank Fresh/Recycle Water Supply w/Motorized Ball Valve Hose Reels HP Hose, Various Lengths



Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



Hydro Engineering, Inc. | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181





Hydroblaster Pressure Washer

7/3000 EHOV - Electric Motor, Hot Water Pressure Washer

Specifications

Volume - GPM (LPM) 7 (26.5) Pressure - PSI (BAR) 3000 (207) **BTU Minimum Supply** 630000 Exhaust Diameter - Inch (mm) 10 (254) Electric Motor - HP (KW) 15 (11.19) Dimensions, Inches (cm) 45 (114.3) L x 32 (81.3) W x 54 (137.16) H Weight, Lbs (kg) 1095 (497) Frame 5BK169 (Sm.) Coil 20" Burner HD-501PC SS Trim - Height 54 3/4" Standard

| Volts (60Hz) | 230V-3P | 460V-3P |
|--------------|---------|---------|
| Amps (60Hz) | 36 | 18 |

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



Hydro Engineering, Inc. | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181 Subject to change without notice

